



Model M1

Professional AV Headset



Model SBJ-5
XLR5M Adapter



Model SBJ-3
XLR4F Adapter



Designed for use in professional audio and video in-truck applications. Interchangeable comm cord means versatility. Matches industry standard electrical specifications for microphone and earphone impedances.

- Fully flexible, rotatable microphone boom
- Protein leather ear pad
- Compatible with SBJ Series adapters
- Custom cables available
- Headset travel bag, SBJ-3, SBJ-5 adapters, and cord clips included



Have a special request?

Call 800-593-6501

Email Sales@dalcommtech.com



© 2020 Dalcomm Tech LLC All features, functionality and other product specifications are subject to change without notice or obligation. No warranty or guarantee expressed or implied is made regarding the capacity, performance or suitability of any product.

Technical Data

A								<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Revise</th> <th>Mark</th> <th>Description</th> <th>Reason</th> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>	Revise	Mark	Description	Reason					A																																
Revise								Mark	Description	Reason																																							
B	<p style="text-align: center;">Specification</p> <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th colspan="2">MIC</th> <th colspan="2">SPK</th> </tr> <tr> <td>Dimension</td> <td>ø19.6x9.5mm</td> <td>Dimension</td> <td>ø30x9.8mm</td> </tr> <tr> <td>Sensitivity</td> <td>0-69dB±3dB</td> <td>Impedance</td> <td>300 Ohm</td> </tr> <tr> <td>Directivity</td> <td>moving-coil</td> <td>S. P. L.</td> <td>114dB±3</td> </tr> </table>							MIC		SPK		Dimension	ø19.6x9.5mm	Dimension	ø30x9.8mm	Sensitivity	0-69dB±3dB	Impedance	300 Ohm	Directivity	moving-coil	S. P. L.	114dB±3	B																									
MIC								SPK																																									
Dimension	ø19.6x9.5mm	Dimension	ø30x9.8mm																																														
Sensitivity	0-69dB±3dB	Impedance	300 Ohm																																														
Directivity	moving-coil	S. P. L.	114dB±3																																														
C	<p style="text-align: center;">Male connector pinpoint</p>							C																																									
D								<p style="text-align: center;">φ2.5±0.1 Black PU Cable 1200±20</p>							D																																		
E	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>6</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>XL male connector</td> <td>5P</td> <td>1pcs</td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>2.5mm straight cable</td> <td>1SC+3C</td> <td>mm</td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>MIC</td> <td>unamplified dynamic mic</td> <td>1pcs</td> <td>200ohm</td> <td></td> </tr> <tr> <td>1</td> <td>Light weight headset</td> <td></td> <td>1pcs</td> <td></td> <td></td> </tr> <tr> <td colspan="6" style="text-align: center;">Bill of Materials</td> </tr> </table>				6													5						4	XL male connector	5P	1pcs			3	2.5mm straight cable	1SC+3C	mm			2	MIC	unamplified dynamic mic	1pcs	200ohm		1	Light weight headset		1pcs			Bill of Materials	
6																																																	
5																																																	
4	XL male connector	5P	1pcs																																														
3	2.5mm straight cable	1SC+3C	mm																																														
2	MIC	unamplified dynamic mic	1pcs	200ohm																																													
1	Light weight headset		1pcs																																														
Bill of Materials																																																	
F	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;"></td> <td colspan="2" style="text-align: center;">Dalcomm Tech LLC</td> </tr> <tr> <td colspan="3">Product Name: Model M-1</td> <td>Version: A</td> </tr> <tr> <td colspan="2">Product No:</td> <td colspan="2">File No:</td> </tr> <tr> <td>Unit: mm</td> <td>Scale: N/A</td> <td colspan="2">Page 1 / 1 Page</td> </tr> <tr> <td colspan="2">Drawn by: Frank Huang</td> <td>Date: 2020.04.15</td> <td rowspan="2">Customer Approval:</td> </tr> <tr> <td colspan="2">Checked by:</td> <td>Date:</td> </tr> <tr> <td colspan="2">Approved by:</td> <td>Date:</td> <td></td> </tr> <tr> <td colspan="4" style="text-align: right;">YF-WI-001REV. 01</td> </tr> </table>									Dalcomm Tech LLC		Product Name: Model M-1			Version: A	Product No:		File No:		Unit: mm	Scale: N/A	Page 1 / 1 Page		Drawn by: Frank Huang		Date: 2020.04.15	Customer Approval:	Checked by:		Date:	Approved by:		Date:		YF-WI-001REV. 01				F										
								Dalcomm Tech LLC																																									
Product Name: Model M-1			Version: A																																														
Product No:		File No:																																															
Unit: mm	Scale: N/A	Page 1 / 1 Page																																															
Drawn by: Frank Huang		Date: 2020.04.15	Customer Approval:																																														
Checked by:		Date:																																															
Approved by:		Date:																																															
YF-WI-001REV. 01																																																	

General

Operating Temperature: -4° to 131° F (-20° to 55° C)

Storage Temperature: -30° to 158° F (-22° to 70° C)

Usage and Care Instructions

- Microphone response is directly affected by its position. The microphone must be positioned very near the wearer's lips, approximately ¼" away from the lips.
- Communications headsets should be cleaned regularly, using alcohol wipes or water and mild soap. They contain electronic elements and should not be immersed in water.
- For the sake of hygiene, it is recommended that the ear pad and microphone cover be cleaned or replaced for each user.

Dalcomm Tech service questions may be directed to: Service@DalcommTech.com

For a list of authorized service and repair facilities please visit: <https://dalcommtech.com/contact>